






KETTENRÄDER FÜR ROLLENKETTEN – DIN 8188 „ASA“

ASA 40

12,7 x 7,95 mm
 Rollen Ø 7,95 mm
 08A - 1 - 2

B1	B2	B3	b1	C	r3
7,2	21,4		7	1,6	13,5



Werkstoff Stahl C45

Z	de	dp	einfach				zweifach				dreifach				
			dm	D1	A	kg	dm	D2	A	kg	dm	D3	A	kg	
8	39,3	33,18													
9	43,2	37,13	24	10	25	0,09									
10	47,2	41,10	26	10	25	0,12	28	10	32	0,19					
11	51,2	45,07	29	10	25	0,14									
12	55,2	49,07	33	10	28	0,20	35	12	35	0,29					
13	59,2	53,06	37	10	28	0,26	38	12	35	0,35					
14	63,2	57,07	41	10	28	0,32	42	12	35	0,43					
15	67,2	61,09	45	10	28	0,38	46	12	35	0,52					
16	71,2	65,10	50	12	28	0,45	50	16	38	0,62					
17	75,2	69,11	52	12	28	0,50	54	16	38	0,73					
18	79,2	73,14	56	12	28	0,58									
19	83,3	77,16	60	12	28	0,67	62	16	38	0,97					
20	87,3	81,19	64	12	28	0,77									
21	91,3	85,22	68	14	28	0,84	70	16	40	1,28					
22	95,4	89,24	70	14	28	0,91	70	16	40	1,37					
23	99,4	93,27	70	14	28	0,94	70	16	40	1,46					
24	103,4	97,29	70	14	28	0,97	75	16	40	1,63					
25	107,4	101,33	70	14	28	1,01	80	16	40	1,82					
26	111,5	105,36	70	16	30	1,09	85	16	40	2,01					
27	115,5	109,40	70	16	30	1,13	85	16	40	2,12					
28	119,5	113,42	70	16	30	1,16	90	16	40	2,33					
29	123,6	117,46	80	16	30	1,41									
30	127,6	121,50	80	16	30	1,46	100	16	40	2,79					
31	131,6	125,54													
32	135,7	129,56	90	16	30	1,78									
33	139,7	133,60													
34	143,8	137,64	90	16	30	1,87									
35	147,8	141,68	90	16	30	1,92	100	16	40	3,40					
36	151,8	145,72	90	16	35	2,21									
37	155,9	149,76													
38	159,9	153,80	90	16	35	2,32									
39	163,9	157,83	90	16	35	2,37									
40	168,0	161,87	90	16	35	2,43									