






KETTENRÄDER FÜR ROLLENKETTEN – DIN 8188 „ASA“

ASA 50

15,875 x 9,53 mm
 Rollen Ø 10,16 mm
 10A - 1 - 2

B1	B2	B3	b1	C	r3
8,7	26,5		8,4	2	17



Werkstoff Stahl C45

Z	de	dp	einfach				zweifach				dreifach			
			dm	D1	A	kg	dm	D2	A	kg	dm	D3	A	kg
8	48,4	41,48	25	10	25	0,11								
9	53,3	46,42	30	10	25	0,16								
10	58,3	51,37	35	10	25	0,22	35	12	40	0,37				
11	63,2	56,34	37	12	30	0,29								
12	68,2	61,34	42	12	30	0,37	44	16	40	0,54				
13	73,2	66,32	47	12	30	0,46	49	16	40	0,67				
14	78,2	71,34	52	12	30	0,56	54	16	40	0,82				
15	83,2	76,36	57	12	30	0,67	59	16	40	0,97				
16	88,3	81,37	60	12	30	0,75	64	16	45	1,25				
17	93,3	86,39	60	12	30	0,87	69	16	45	1,45				
18	98,3	91,42	70	14	30	1,00								
19	103,3	96,45	70	14	30	1,15	79	16	45	1,67				
20	108,4	101,49	75	14	30	1,20	84	16	45	2,14				
21	113,4	106,52	75	16	30	1,35	85	16	45	2,27				
22	118,4	111,55	80	16	30	1,40	90	16	45	2,54				
23	123,5	116,58	80	16	30	1,47	95	16	45	2,81				
24	128,5	121,62	80	16	30	1,53	100	16	45	3,11				
25	133,6	126,66	80	16	30	1,60	105	16	45	3,14				
26	138,6	131,70	85	20	35	1,96	110	20	45	3,74				
27	143,6	136,75	85	20	35	2,03	110	20	45	3,94				
28	148,7	141,78	90	20	35	2,25	115	20	45	4,28				
29	153,7	146,83	90	20	35	2,33								
30	158,8	151,87	90	20	35	2,41								
31	163,8	156,92	95	20	35	2,64								
32	168,9	161,95	95	20	35	2,73								
33	173,9	167,00	95	20	35	2,82								
34	178,9	172,05	95	20	35	2,91								
35	184,0	177,10	95	20	35	3,01								
36	189,0	182,15	100	20	35	3,26								
37	194,1	187,20	100	20	35	3,36								
38	199,1	192,24	100	20	35	3,47								
39	204,2	197,29	100	20	35	3,57								
40	209,2	202,34	100	20	35	3,68								