






KETTENRÄDER FÜR ROLLENKETTEN – DIN 8188 „ASA“

ASA 60

19,05 x 12,7 mm
 Rollen Ø 11,91 mm
 12A - 1 - 2

B1 B2 B3 b1 C r3

11,6 34,1 11,3 2,4 20



Werkstoff Stahl C45

Z	de	dp	einfach				zweifach				dreifach			
			dm	D1	A	kg	dm	D2	A	kg	dm	D3	A	kg
8	58,1	49,78												
9	64,0	55,70												
10	70,0	61,64	42	12	30	0,38	42	16	45	0,58				
11	76,0	67,61	46	16	35	0,50	47	16	50	0,80				
12	81,9	73,60	52	16	35	0,64	53	16	50	1,01				
13	87,9	79,59	58	16	35	0,80	59	16	50	1,24				
14	94,0	85,61	64	16	35	0,97	65	16	50	1,45				
15	100,0	91,63	70	16	35	1,16	71	16	50	1,73				
16	106,0	97,65	75	16	35	1,34	77	20	50	2,03				
17	112,0	103,67	80	16	35	1,53	83	20	50	2,35				
18	118,0	109,71	80	16	35	1,61	89	20	50	2,70				
19	124,1	115,75	80	16	35	1,70	95	20	50	3,06				
20	130,1	121,78	80	16	35	1,84	100	20	50	3,45				
21	136,2	127,82	90	20	40	2,35	100	20	50	3,69				
22	142,2	133,86	90	20	40	2,45	100	20	50	3,96				
23	148,2	139,90	90	20	40	2,56	110	20	50	4,50				
24	154,3	145,94	90	20	40	2,67	110	20	50	4,81				
25	160,3	152,00	90	20	40	2,79	120	20	50	5,40				
26	166,4	158,04	95	20	40	3,08	120	20	50	5,73				
27	172,4	164,09	95	20	40	3,21								
28	178,5	170,13	95	20	40	3,34	120	20	50	6,43				
29	184,5	176,19												
30	190,6	182,25	95	20	40	3,62	120	20	50	7,18				
31	196,6	188,31												
32	202,7	194,35	95	20	40	3,92								
33	208,8	200,40												
34	214,8	206,46	95	20	40	4,25								
35	220,9	212,52	95	20	40	4,41								
36	226,9	218,58	95	20	40	4,71								
37	233,0	224,64												
38	239,0	230,69	100	20	40	5,07								
39	245,1	236,75												
40	251,1	242,81	100	20	40	5,45								