




ZAHNRIEMENRÄDER PROFIL HTD® FÜR TAPERBUCHSEN


5M

Teilung 5 mm


für Zahnriemenbreite 15 mm




10



10F



13



15F

Werkstoff: Stahl

| code | Typ | Werkstoff | Zähne- zahl | Spann- buchsentyp | Bohrung max | dp | de | Df | Dm | Di | F | L | R | Nr. Bordscheiben | kg |
|-------------|-----|-----------|----------------|----------------------|----------------|--------|--------|-----|-----|-----|----|----|----|---------------------|------|
| TL 34 5M 15 | 15F | St | 34 | 1008 | 25 | 54,11 | 52,97 | 57 | | | 22 | 22 | | 213 | 0,20 |
| TL 36 5M 15 | 15F | St | 36 | 1108 | 25 | 57,30 | 56,15 | 60 | | | 22 | 22 | | 214 | 0,25 |
| TL 38 5M 15 | 15F | St | 38 | 1108 | 25 | 60,48 | 59,34 | 66 | | | 22 | 22 | | 216 | 0,30 |
| TL 40 5M 15 | 15F | St | 40 | 1108 | 25 | 63,66 | 62,52 | 71 | | | 22 | 22 | | 217 | 0,35 |
| TL 44 5M 15 | 15F | St | 44 | 1108 | 25 | 70,03 | 68,89 | 75 | | | 22 | 22 | | 218 | 0,40 |
| TL 48 5M 15 | 10F | St | 48 | 1210 | 32 | 76,39 | 75,25 | 83 | 59 | | 22 | 25 | 3 | 219 | 0,46 |
| TL 56 5M 15 | 10F | St | 56 | 1210 | 32 | 89,13 | 87,99 | 93 | 70 | | 22 | 25 | 3 | 222 | 0,60 |
| TL 64 5M 15 | 10F | St | 64 | 1210 | 32 | 101,86 | 100,72 | 106 | 80 | | 22 | 25 | 3 | 224 | 0,80 |
| TL 72 5M 15 | 10 | St | 72 | 1610 | 42 | 114,59 | 113,45 | | 92 | | 22 | 25 | 3 | | 1,20 |
| TL 80 5M 15 | 10 | St | 80 | 1610 | 42 | 127,32 | 126,18 | | 92 | | 22 | 25 | 3 | | 1,76 |
| TL 90 5M 15 | 10 | St | 90 | 1610 | 42 | 143,24 | 142,10 | | 92 | | 22 | 25 | 3 | | 2,32 |
| TL112 5M 15 | 10 | St | 112 | 2012 | 50 | 178,25 | 177,11 | | 110 | | 20 | 32 | 12 | | 3,72 |
| TL136 5M 15 | 13 | St | 136 | 2012 | 50 | 216,45 | 215,31 | | 110 | 199 | 20 | 32 | 6 | | 3,82 |