




# ZAHNRIEMENRÄDER „PCB“ POLYCHAIN FÜR TAPERBUCHSEN


## 8M

Teilung 8 mm


für Zahnriemenbreite 12 mm



2F



10F



10

Werkstoff: Stahl

Werkstoff: Grauguss (GG)

Beschreibung	Artikelnr.	Typ	Werkstoff	Zähnezahl	Spanbuchsentyp	Bohrung max.	dp	de	Df	Dm	Di	F	L	R	d	Nr. Bordscheiben	kg
8M 22S 12	PCB47012022	2F	St	22			56,02	54,42	60	43	20	30	10	12	308	0,43	
TL 8M 25S 12	PCB47012025	10F	St	25	1108	28	63,66	62,06	66	49	20	22	2		310	0,25	
TL 8M 28S 12	PCB47012028	10F	St	28	1108	28	71,30	69,70	75	56	20	22	2		312	0,37	
TL 8M 30S 12	PCB47012030	10F	St	30	1210	32	76,39	74,79	83	60	20	25	5		314	0,41	
TL 8M 32S 12	PCB47012032	10F	St	32	1610	42	81,49	79,89	87	66	20	25	5		315	0,43	
TL 8M 34S 12	PCB47012034	10F	St	34	1610	42	86,58	84,98	91	68	20	25	5		316	0,45	
TL 8M 36S 12	PCB47012036	10F	St	36	1610	42	91,67	90,07	98	74	20	25	5		319	0,59	
TL 8M 38S 12	PCB47012038	10F	St	38	1610	42	96,77	95,17	103	80	20	25	5		320	0,70	
TL 8M 40S 12	PCB47012040	10F	St	40	1610	42	101,86	100,26	106	85	20	25	5		321	0,82	
TL 8M 45S 12	PCB47012045	10F	St	45	2012	50	114,59	112,99	119	92	20	32	12		325	1,10	
TL 8M 48S 12	PCB47012048	10F	St	48	2012	50	122,23	120,63	127	100	20	32	12		327	1,42	
TL 8M 50S 12	PCB47012050	10F	St	50	2012	50	127,32	125,72	135	104	20	32	12		328	1,60	
TL 8M 56S 12	PCB47012056	10F	St	56	2012	50	142,60	141,00	148	104	20	32	12		333	2,10	
TL 8M 60S 12	PCB47012060	10F	St	60	2012	50	152,79	151,19	158	111	20	32	12		335	2,40	
TL 8M 64S 12	PCB47012064	10F	St	64	2012	50	162,97	161,37	168	111	20	32	12		338	2,70	
TL 8M 75S 12	PCB47012075	10	GG	75	2012	50	190,99	189,39		111	20	32	12			3,70	
TL 8M 80S 12	PCB47012080	10	GG	80	2012	50	203,72	202,12		111	20	32	12			4,40	
TL 8M 90S 12	PCB47012090	10	GG	90	2012	50	229,18	227,58		111	20	32	12			5,50	